



DSW-2



MADE IN GERMANY

Wassermann is a medium-sized, owner-operated company with head office in Hamburg. We design and produce high-quality technical devices in Germany. Our main users are dental laboratories, dental clinics and various industrial areas worldwide.

Why a Wassermann product?

Wassermann products are manufactured from high-quality materials and the proportion of plastics used is intentionally kept as low as possible. Our devices are known for their suitability for daily use, functionality and longevity. As a result, the users place high levels of trust in the Wassermann brand. We feel it is our duty to support our customers on a daily basis when it comes to safety, service and productivity. Technological perfection, optimum quality and especially sustainability are the benchmarks we set. Thanks to the combination of these values, the family-owned company, since its establishment in 1927, has gained worldwide recognition as a manufacturer of high-quality products.



Further information are available on our website at www.wassermann.hamburg

Your Dental Dealer _____

DSW-2/4K and DSW-2



Dosing Scales



Wassermann Dental-Maschinen GmbH
Rudorffweg 15-17 · 21031 Hamburg · Germany
Phone: +49 (0)40 730 926-0 · Fax: +49 (0)40 730 37 24
info@wassermann-dental.com · www.wassermann.hamburg

Dosing Scales DSW-2/4K & DSW-2

Indispensable for precise mixing: The DSW-2 and DSW-2/4 K dosing scales make it easy to get exact mixing ratios and reproducible results. The powder is weighed, the required amount of liquid will be added automatically. All pumps can be individually controlled. The DSW-2/4 K has also a special cooling system to keep the liquid at the set temperature (17°C, 19°C or 21°C).

DSW-2/4K
with temperature
ranges cooling
system

Durable housing,
plastic powder coated



Large, clear LCD display

Memory for up to
30 mixing recipes

Scales in high-quality stainless steel,
easy to clean

Major Features

- Precision scales for modern dosing and weighing technologies
- For mixing all common plasters and embedding materials
- Constant mixing ratios of powder and liquids
- Extremely durable, easy to clean housing
- DSW-2/4K comes as standard with 4 pumps for cooled liquids, it is possible to add 2 additional pumps (non-cooled)
- DSW-2 comes as standard with 1 pump non-cooled, it is possible to add 5 additional pumps (non-cooled)
- **Included in delivery:**
DSW-2/4K with 4 pumps, cooled
DSW-2 with 1 pump, non-cooled

Accessories

Upgrade at one pump, non-cooled

Item no.

390030

DSW-2/4K
DSW-2

Item no. 172989
Item no. 172988

Voltage	220–240 V / 50/60 Hz
Power consumption DSW-2/4K	0.7 A
Power consumption DSW-2	0.5 A
Output DSW-2/4K	100 W
Output DSW-2	75 W
W x H x D	210 x 470 x 410 mm
Weight DSW-2/4K	17.5 kg
Weight DSW-2	13.0 kg
Weighing range	min.=5 g, max.=6000 g, min. dosing quantity (e)=2 g
Weighing accuracy	+/- 0.5 g
Temperature operative range	5 – 35 °C
Temperature ranges cooling system DSW-2/4K	17°C, 19°C, 21°C